



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DP-70P

TECHNICAL DATA SHEET:

**DYNAMIC POLYMERS DP-70P IS A FISCHER TROPSCH
HYDROCARBON REFINED WAX DESIGNED FOR THE PVC INDUSTRY.**

Characteristics	Specification
Congealing point °C	72
Drop Point °C	76
Color	30
Viscosity CP (100°C)	4-6
Penetration (25°C)	10
Odor Range 1-4	1
Thermal Stability (125°C)	24
Anti-oxidants	—
Acid Value	< 0.1
Bromine value	≤0.1
Saponification	< 0.5
Apperance	Pastilles, Flakes
Package	25KG/Bag

END USE/MARKETS:

- › PVC
- › MASTERBATCH
- › SPECIALTY APPLICATION

STANDARD PACKAGING:

DP-70P IS PACKAGED IN 25 KG BAGS

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.